

Product Code: **UL7208B0**

Product Description: **Hot-rolled non-alloy steel, not in coils, width ≥ 600 mm**

World Trade (2023): **23.8 Billion €**

This ExportPlanning Product Code represents the aggregate of the Combined Nomenclature codes shown in the left column of the following table. In order to provide an overview of the aggregation criteria followed, in the column "Description" are also reported similar categories to that of the products included in this ExportPlanning Product Code. Column "Weight %", also reported the percentage weight of each code of Combined Nomenclature with respect to aggregation considered. **This weight is determined by taking the structure of imports of the European Union.**

CHAPTER 72 - IRON AND STEEL		
CATEGORIES: products of iron or non-alloy steel, of a width of 600 mm or more, hot-rolled, not clad, plated or coated		
Code	Weight %	Description
		-In coils, not further worked than hot-rolled, with patterns in relief
		-Other, in coils, not further worked than hot-rolled, pickled
		-Other, in coils, not further worked than hot-rolled
7208 40 00	1.7	-Not in coils, not further worked than hot-rolled, with patterns in relief
		-Other, not in coils, not further worked than hot-rolled
		-Of a thickness exceeding 10 mm
7208 51 20	43.7	-Of a thickness exceeding 15 mm
		-Of a thickness exceeding 10 mm but not exceeding 15 mm, of a width of
7208 51 91	4.3	-2050 mm or more
7208 51 98	8.6	-Less than 2050 mm

CHAPTER 72 - IRON AND STEEL

CATEGORIES: products of iron or non-alloy steel, of a width of 600 mm or more, hot-rolled, not clad, plated or coated

Code	Weight %	Description
		-Of a thickness of 4,75 mm or more but not exceeding 10 mm
7208 52 10	0.5	-Rolled on four faces or in a closed box pass, of a width not exceeding 1250 mm
		-Other, of a width of
7208 52 91	4.5	-2050 mm or more
7208 52 99	18.6	-Less than 2050 mm
		-Of a thickness of 3 mm or more but less than 4,75 mm
7208 53 10	0.3	-Rolled on four faces or in a closed box pass, of a width not exceeding 1250 mm and of a thickness of 4 mm or more
7208 53 90	7.8	-Other
7208 54 00	2.5	-Of a thickness of less than 3 mm
		-Other
7208 90 20	0.3	-Perforated
7208 90 80	7.1	-Other